



TECHNICAL SHEET



FA 20 600 06

Designation: Retractable Fall Arrester Olympe in wire rope


- Steel wire rope diam. 4.8 mm
- Casing made up of aluminium alloy
- Minimum breaking strength : > 12 kN

Connectors:


1 screw-locking karabiner opening 17 mm ref. FA 50 101 17, and 1 snap hook with swivel and fall indicator, opening 21 mm.

Compliance: Conforms to EN 360:2002.

136 kg



- Certified for a horizontal use when used with the lanyard ref. FA4030415 connected to the wire rope of the block.



Length: 6 mtrs.

Materials of the components:

Casing: Aluminium Alloy
Wire rope: Galvanized steel
Connectors: Steel.

HS code	Carton Size / Pieces	Unit Weight
84289090	60x40x24 / 04	4.40 Kg

AET : N° 4036 Issue 4 Extension 1

Satra Technology Centre, N°0321
Wyndham Way, Telford Way, Kettering,
Northamptonshire, NN16 8SD, United Kingdom.

Article 11: GB07/73551

SGS United Kingdom Ltd., N° 0120
Unit 202B, Worle Parkway,
Weston-super-Mare, BS22 6WA, United Kingdom



MAJ : 02/15

ZI les portes du Dauphiné

4 rue de l'Aigüe
69 780 St Pierre de Chandieu – France
Tel : +33 (0)4 72 48 78 27 Fax : + 33 (0)4 72 48 58 32
www.kratossafety.com info@kratossafety.com

